

Features

- ▶ Typical wavelength, 808nm (Invisible)
 - ▶ Stabilized optical power 100mW
 - ▶ Single supply voltage, 5V DC
 - ▶ Modulation : digital, analog ~300KHz
 - ▶ Line generator
 - ▶ Cylindrical glass lens
 - ▶ Wire length : 30cm(standard) or custom
 - ▶ Laser class : 3R, 3B (IEC 60825-1)
- ◆ Option : Bracket & Power supply.

Specification

Optical

Optical power(mW)	100 (Tc=25°C)
LD power(mW)	200 (Max)
Wavelength(nm)	808 ±15
Collimated Beam Wid(mm)	<3 (at 10m)
Fan Angle (°)	15,30,45,60,90, 120
Line Pattern	Accurate Straight
Beam Quality	TEM00
Beam intensity Pattern	Gaussian
LD Pin Connection	Case Ground

Electrical

Operating voltage(DC V)	5 ± 5%
Operating current(mA)	100 (Typ.)
Drive circuit	APC
Operating Temp.(°C)	-10 ~ +60
Storage Temp.(°C)	-40 ~ +85

Mechanical


Weight(g)	24 ± 0.5
Dimensions(mm)	14Φ X 80
Operating lifetime(h)	30,000~50,000 (@RT)
Housing material	Aluminum

Description

The MK series laser diode module combines laser diode technology, quality optics, and sophisticated electronics within a slim and light aluminum anodized Housing for variety of applications. This series of modules provides a high-brightness elliptical laser line, and have various wavelengths and optical output power.

Applications include a measurement, positioning, lighting, alignment, guidelines, pointing, switching, leveling, and machine vision etc. Useful in a variety of medical, industrial, and scientific instrumentation, as well as general R&D work.

Drawings



* Range of fan angle

Symbol	Angle	Line length [mm] (distance 1m)	
		Perpendicular	Inclined at45°
1D	15°	250	500
3D	30°	500	1200
4D	45°	830	2000
6D	60°	1160	3500
9D	90°	2000	About 5000
12D	120°	3400	About 8000

Lanics Co., Ltd.

Room #703, 7F Woolim e-Biz Center
170-5, Guro-dong, Guro-gu, Seoul, 152-050, Korea
TEL : +82-2-2108-2255 FAX : +82-2-2108-2260

E-mail : support@lanics.com

http:// www.lanics.com